

PassTest

Bessere Qualität , bessere Dienstleistungen!



Q&A

<http://www.passtest.de>

Einjährige kostenlose Aktualisierung

Exam : **210-010**

Title : VCE Vblock™ Systems
Deployment and
Implementation - Core Exam

Version : DEMO

1. When powering on a Vblock System what is the correct power up sequence?

- A. Switches, AMP, SAN, UCS chassis, and UCS blades
- B. Switches, SAN, UCS chassis, UCS blades, and AMP
- C. Switches, AMP, UCS chassis, UCS blades, and SAN
- D. Switches, SAN, AMP, UCS chassis, and UCS blades

Answer: A

2. What are three primary site survey considerations? (Choose three.)

- A. Site information
- B. Technical resources
- C. Customer power requirements
- D. Data center physical audit
- E. Disaster recovery plan

Answer: A,C,D

3. Which EMC software is required to initialize a Vblock System 200 storage array?

- A. Unisphere Service Manager
- B. Unisphere Server Utility
- C. VNX Installation Assistant
- D. Unisphere Client

Answer: C

4. Which EMC software is required to upgrade code on a Vblock System 200 storage array?

- A. Unisphere Service Manager
- B. Unisphere Server Utility
- C. VNX Installation Assistant
- D. Unisphere Client

Answer: A

5. Which two statements are correct about Vblock System Release Certification Matrix (RCM) upgrades? (Choose two.)

- A. The RCM must be applied by VCE certified resources.
- B. When upgrading to a new RCM, all components may not require an upgrade.
- C. The most recent RCM version must be applied.
- D. An addendum to the RCM may be issued to address a bug or software issue.

Answer: B,D

6. Which Cisco Catalyst switch is used for network management on a Vblock System 200?

- A. Cisco Catalyst 2960
- B. Cisco Catalyst 3560
- C. Cisco Catalyst 3750
- D. Cisco Catalyst 4500

Answer: C

7. In addition to the Logical Configuration Survey (LCS), which document is required prior to manufacturing a Vblock System 720?

- A. Configuration Reference Guide
- B. VCE change control form
- C. VCE Vblock Systems Release Certification Matrix
- D. EMC bin file request form

Answer: D

8. For bare metal deployments, which statement ensures VCE is able to provide reasonable-effort support?

- A. The ratio of bare metal to virtualized hosts cannot be more than 40 percent.
- B. A minimum of five virtualized hosts must be enabled.
- C. Bare metal workloads are run on separate physical spindles, disk groups, and pools.
- D. Systems cannot include hypervisor technologies other than VMware.

Answer: C

9. Customers provide the information used to develop the Logical Configuration Survey (LCS) before manufacturing begins.

What information is required? (Choose two.)

- A. syslog server IP address
- B. NTP server IP address
- C. method of device access (telnet or SSH)
- D. MIB browser IP address

Answer: B,C

10. The implementation profile located in the Logical Configuration Survey (LCS) identifies if the customer will be using which two solutions? (Choose two.)

- A. EMC SnapView
- B. Cisco IAC
- C. Cisco Unified Communications
- D. VMware vCloud Director

Answer: C,D

11. What are three requirements of the Vblock System test plan? (Choose three.)

- A. All tests identified in the test plan must be executed.
- B. Observed results must be documented by a VCE certified resource.
- C. Tests are confidential and must not be performed in view of the customer.
- D. Once tests are completed, the customer must sign the test plan document.
- E. A completed test plan must be submitted to the VCE project manager.

Answer: B,D,E

12. Which test is only performed on a Vblock System 320 that contains a high availability Advanced Management Pod (HA-AMP)?

- A. Cisco blade server failure test

- B. Cisco UCS single power supply failure test
- C. Cisco Catalyst 3560 failure and recovery test
- D. Cisco UCS C220 failover test

Answer: D

13. Your manager asks you to configure an external Syslog on VMware ESXi hosts. In which two ways would the Syslog be configured? (Choose two.)

- A. using the vSphere client
- B. using the esxcli system syslog command
- C. using VMware Update Manager
- D. using the VMware SQL database

Answer: A,B

14. When performing hardware maintenance on a Cisco UCS B-Series blade, which GUI parameter should be selected before removing the blade out of the chassis?

- A. Remove
- B. Re-acknowledge
- C. Decommission
- D. Diagnostic Interrupt

Answer: C

15. A customer notices a failed drive error for a Vblock System 320 storage array on an EMC Unisphere screen.

Which logs must be collected and sent to VCE support to confirm that the drive has failed?

- A. SPcollects
- B. NAR files
- C. symapi.log
- D. EMC Grab

Answer: A

16. A customer wants to ensure that the new installed Vblock System 320 storage array is being monitored by EMC.

Which EMC monitoring tool must be installed to accomplish this?

- A. Data Center Network Manager (DCNM)
- B. EMC Secure Remote Support (ESRS)
- C. EMC OnAlert
- D. ConnectEMC

Answer: B

17. Which two steps are required to complete a Cisco UCS Smart Call Home registration on a Vblock System? (Choose two.)

- A. After receiving the e-mail response from Cisco, click the link in the e-mail to complete registration for Smart Call Home.
- B. Select "Send System Inventory Now" in UCSM.

- C. Configure UCSM to send periodic system inventory messages.
- D. Configure the SNMP trap destination.

Answer: A,B

18.Which port is used for communication between EMC Secure Remote Support (ESRS) and the Policy Manager?

- A. 443
- B. 5414
- C. 8090
- D. 8443

Answer: D

19.You are backing up a Cisco UCS configuration.

Which parameter should you select to retain assigned vHBAs, WWPNs, vNICs MACs, WWNNs, and UUIDs?

- A. Retain Identities
- B. Preserve Identities
- C. Include Identities
- D. Copy Identities

Answer: B

20.Which Cisco management software is required to setup EMC e-mail home for Cisco MDS switches?

- A. Cisco Data Center Network Manager (Cisco DCNM-SAN)
- B. Cisco Unified Computing System Manager (Cisco UCSM)
- C. Cisco Smart Call Home (Cisco SCH)
- D. Cisco Terminal Access Controller Access Control System (Cisco TACACS)

Answer: A