

PassTest

Bessere Qualität , bessere Dienstleistungen!



Q&A

<http://www.passtest.de>

Einjährige kostenlose Aktualisierung

Exam : 700-501

**Title : SMB Specialization for
Engineers**

Version : DEMO

1. When you design a customer network that is composed only of a pure Layer 2 switch and a router, which feature should you enable to support communication among VLANs?

- A. VLANs cannot communicate when only a router and a Layer 2 switch are used in the design.
- B. Spanning Tree on the Layer 2 switch
- C. Static routes on the Layer 2 switch
- D. Trunking between the Layer 2 switch and the router
- E. Uplink port aggregation on the router

Answer: D

2. Which statement about Cisco CleanAir technology is true?

- A. It features chip-level proactive and automatic interference mitigation.
- B. It features chip-level proactive and automatic electronic beam forming.
- C. It features automatic advanced radio frequency shaping.
- D. It is a feature of the Cisco Aironet 1600 Series AP

Answer: A

3. Which three options can be connected directly to a Cisco Nexus switch? (Choose three.)

- A. Token ring network
- B. Storage area network
- C. Server cluster
- D. Local area network
- E. 4G network
- F. Wide area network

Answer: B, C, D

4. Which two product portfolios help make up the FlexPod Express solution? (Choose two.)

- A. Cisco Nexus 5000
- B. Cisco ISR 1900, 2900, and 3900 Series
- C. Cisco UCS E-Series Servers
- D. Cisco Nexus 3048 Switch
- E. Cisco ISR 2900 and 3900 Series
- F. Cisco UCS C-Series Server

Answer: D, F

5. Which three options are pillars of the Cisco Security Intelligence Operations? (Choose three.)

- A. Dynamic updates
- B. OpenBTS Database
- C. Cloud base
- D. Threat Operations Center

E.Sensor base

F.Manual updates

Answer: A, D, E

Explanation:

Cisco SIO is composed of three pillars: Cisco SensorBas, a comprehensive threat database; Threat Operations Center with 500 security analysts and constant dynamic updates fed to Cisco security devices.