

# *PassTest*

Bessere Qualität , bessere Dienstleistungen!



## Q&A

<http://www.passtest.de>

Einjährige kostenlose Aktualisierung

**Exam** : **JN0-201**

**Title** : Juniper networks Certified  
internet  
associate.m(jncia-m)

**Version** : DEMO

1. Firewall filters can be used to accept, discard, or reject packets based on \_\_\_\_\_. (Choose three.)

- A. protocol type
- B. MAC address
- C. TCP or UDP port
- D. source and destination IP address

**Answer:** ACD

2. A firewall filter is applied as an input filter on a transit interface. What three types of traffic will this affect?

(Chose three.)

- A. inbound traffic transiting the router
- B. outbound traffic transiting the router
- C. traffic destined to the Routing Engine
- D. traffic destined to the interface address on which the filter is applied

**Answer:** ACD

3. By default, which command can be used to display information about packets that have been logged with the syslog firewall filter action?

- A. show log
- B. show firewall
- C. show log messages
- D. show firewall log

**Answer:** C

4. During OSPF adjacency formation, in what state is a router when it is negotiating to be in charge of the database synchronization process?

- A. Init
- B. 2Way
- C. ExStart
- D. Exchange

**Answer:** C

5. Why would you make a non-backbone area a stub or not-so-stubby area?

- A. to aggregate routes learned from the ABR
- B. to lower the cost of routes advertised by the ABR
- C. to connect a non-contiguous area to the backbone
- D. to decrease the size of the link-state database in that area

**Answer: D**

6. What is the purpose of the OSPF link-state update packet?

- A. describes a change to the OSPF hello timer
- B. carries one or more link-state advertisements
- C. establishes and maintains neighbor relationships
- D. describes the contents of the entire link-state database

**Answer: B**

7. If all OSPF routers on a broadcast network have the same OSPF priority, what parameter is used to determine the new BDR at the time of a DR failure?

- A. area ID
- B. router ID
- C. loopback address
- D. IP address of interface on broadcast network

**Answer: B**

8. Which CLI command is used to see the current OSPF link-state database?

- A. show ospf database
- B. show ospf neighbor
- C. show protocols ospf
- D. show ospf link-state

**Answer: A**

9. What type of OSPF router is responsible for redistributing routes into OSPF?

- A. ABR
- B. ASBR
- C. internal router
- D. backbone router

**Answer: B**

10. Three IS-IS routers on a broadcast segment have different priority values configured. Which router is elected the DIS on that broadcast segment?

- A. the router with the lowest priority
- B. the router with the highest priority
- C. the router with the highest System ID
- D. the router with the highest IP address

**Answer: B**

11. What are the three components of the ISO NET address? (Choose three.)

- A. Area ID
- B. N-selector
- C. System ID
- D. AS number
- E. ISO number
- F. MAC address

**Answer: ABC**

12. How often are IS-IS Hello packets transmitted?

- A. 3 seconds for DIS; 9 seconds for non-DIS
- B. 9 seconds for DIS; 3 seconds for non-DIS
- C. 10 seconds for DIS; 3 seconds for non-DIS
- D. 10 seconds for all routers

**Answer: A**

13. How do you enable interface fe-0/0/0 under the [edit protocols isis] level to form both a Level 1 and Level 2 adjacency?

- A. set interface fe-0/0/0.0
- B. set interface fe-0/0/0.0 all level
- C. set interface fe-0/0/0.0 level 3 enable
- D. set interface fe-0/0/0.0 level 1 level 2

**Answer: A**

14. What command would you use to view an IS-IS adjacency?

- A. show iso neighbor
- B. show isis neighbor
- C. show iso adjacency
- D. show isis adjacency

**Answer: D**

15. Two Level 2 routers are exchanging Hello packets with different Area IDs. What occurs between these routers?

- A. An Adjacency forms.
- B. An Adjacency does not form.
- C. An Adjacency forms but traffic is not forwarded.
- D. No IS-IS PDUs are sent.

**Answer: A**

16. Assume that a comparable configuration is applied to your peer in AS 11 and that bi-directional TCP reachability has been achieved. Which EBGP configuration will allow the BGP session to become established?

- A. routing-options { autonomous-system 64; } protocols { bgp { group external-peer11 { type external; neighbor 10.0.3.6 { peer-as 11; } } } }
- B. routing-options { autonomous-system 11; } protocols { bgp { group external-peer1 { type external;

```
peer-as 11;{ neighbor 10.0.3.6; } }
```

```
C. routing-options { autonomous-system 11; } protocols { bgp { group external-peer11 { type external; peer-as 64;{ neighbor 10.0.3.6; } group external-peer11 { type external; peer-as 64;{ neighbor 10.0.3.6; } } type external; peer-as 64;{ neighbor 10.0.3.6; } } peer-as 64;{ neighbor 10.0.3.6; } } neighbor 10.0.3.6; } }
```

```
D. routing-options { }
```

```
E. routing-options { autonomous-system 64; }
```

```
F. routing-options { autonomous-system 64; }
```

```
G. routing-options { autonomous-system 64; } protocols {
```

```
H. routing-options { autonomous-system 64; } protocols { bgp { autonomous-system 64; } protocols { bgp { group external-peer101 { } protocols { bgp { group external-peer101 { peer-as 101; protocols { bgp { group external-peer101 { peer-as 101; neighbor 10.0.3.6; protocols { bgp { group external-peer101 { peer-as 101; neighbor 10.0.3.6; } } bgp { group external-peer101 { peer-as 101; neighbor 10.0.3.6; } } group external-peer101 { peer-as 101; neighbor 10.0.3.6; } } peer-as 101; neighbor 10.0.3.6; } } neighbor 10.0.3.6; } } } } }
```

**Answer: A**

17. What is the first step in BGP route selection?

- A. The local router prefers the route with the shortest AS\_PATH.
- B. The router first verifies that it has a route to the BGP Next Hop IP address.
- C. The local router prefers the route from the peer with the lowest peer ID address.
- D. The local router prefers the route learned from an EBGP peer over a route learned from an IBGP peer.

**Answer: B**

18. What are two purposes of the AS\_PATH attribute? (Choose two.)

- A. route selection
- B. loop avoidance
- C. determining equal cost paths for reachabilty
- D. defining the application of other BGP attributes

**Answer: AB**

19. Once the TCP connection is established, which message type initiates the BGP peering process?

- A. Open
- B. Active
- C. Update
- D. Keepalive
- E. Notification

**Answer: A**

20. What are two ways that a valid IBGP peering session can be configured? (Choose two.)

- A. via the accept x.x/y command
- B. via TCP reachable physical interface addresses
- C. via remote loopbacks with the local-address command
- D. via UDP with the neighbor x.x.x.x command at the group level

**Answer: BC**