PassTest

Bessere Qualität , bessere Dienstleistungen!

Q&A

http://www.passtest.de

Einjährige kostenlose Aktualisierung

Exam : **PCNSE7**

Title : Palo Alto Networks Certified Network Security Engineer

Version : DEMO

1.A host attached to Ethernet 1/4 cannot ping the default gateway. The widget on the dashboard shows Ethernet 1/1 and Ethernet 1/4 to be green. The IP address of Ethernet 1/1 is 192.168.1.7 and the IP address of Ethernet 1/4 is 10.1.1.7. The default gateway is attached to Ethernet 1/1. A default route is properly configured.
What can be the cause of this problem?
A. No Zone has been configured on Ethernet 1/4.
B. Interface Ethernet 1/1 is in Virtual Wire Mode.
C. DNS has not been properly configured on the firewall.
D. DNS has not been properly configured on the host.
Answer: A

2.Site-A and Site-B have a site-to-site VPN set up between them. OSPF is configured to dynamically create the routes between the sites. The OSPF configuration in Site-A is configured properly, but the route for the tunner is not being established. The Site-B interfaces in the graphic are using a broadcast Link Type. The administrator has determined that the OSPF configuration in Site-B is using the wrong Link Type for one of its interfaces.



Which Link Type setting will correct the error?
A. Set tunnel. 1 to p2p
B. Set tunnel. 1 to p2mp
C. Set Ethernet 1/1 to p2mp
D. Set Ethernet 1/1 to p2p
Answer: A

3.Given the following table.



Destination	Next Hop	Flags	Age	Interface
10.66.22.0/23	10.66.22.80	A C		ethernet1/5
10.66.22.80/32	0.0.0.0	A H		
10.66.24.0/23	0.0.0.0	R		ethernet1/3
10.66.24.0/23	0.0.0.0	Oi	19567	ethernet1/3
10.66.24.0/23	10.66.24.80	A C		ethernet1/3
10.66.24.80/32	0.0.0.0	A H		
192.168.80.0/24	192.168.80.1	A C		ethernet1/4
192.168.80.1/32	0.0.0.0	A H		
192.168.93.0/30	10.66.24.88	R		ethernet1/3
192.168.93.0/30	10.66.24.93	A Oi	600	ethernet1/3

Which configuration change on the firewall would cause it to use 10.66.24.88 as the next hop for the 192.168.93.0/30 network?
A. Configuring the administrative Distance for RIP to be lower than that of OSPF Int.
B. Configuring the metric for RIP to be higher than that of OSPF Int.
C. Configuring the administrative Distance for RIP to be higher than that of OSPF Ext.
D. Configuring the metric for RIP to be lower than that OSPF Ext.
Answer: A

4.A VPN connection is set up between Site-A and Site-B, but no traffic is passing in the system log of Site-A, there is an event logged as like-nego-p1-fail-psk.
What action will bring the VPN up and allow traffic to start passing between the sites?
A. Change the Site-B IKE Gateway profile version to match Site-A,
B. Change the Site-A IKE Gateway profile exchange mode to aggressive mode.
C. Enable NAT Traversal on the Site-A IKE Gateway profile.
D. Change the pre-shared key of Site-B to match the pre-shared key of Site-A
Answer: D

5.A company is upgrading its existing Palo Alto Networks firewall from version 7.0.1 to 7.0.4.
Which three methods can the firewall administrator use to install PAN-OS 7.0.4 across the enterprise?(Choose three)
A. Download PAN-OS 7.0.4 files from the support site and install them on each firewall after manually uploading.
B. Download PAN-OS 7.0.4 to a USB drive and the firewall will automatically update after the USB drive is inserted in the firewall.
C. Push the PAN-OS 7.0.4 updates from the support site to install on each firewall.
D. Push the PAN-OS 7.0.4 update from one firewall to all of the other remaining after updating one firewall.
E. Download and install PAN-OS 7.0.4 directly on each firewall.
F. Download and push PAN-OS 7.0.4 from Panorama to each firewall.

Answer: ACF